### **AXIOM®-DV-TC**

Height: 17.8" Width: 9.0" Depth: 22.5" (45.2cm) (22.9cm) (57.2cm)



Server(s) sold separately

- · Adjusts automatically to varying water pressure
- For high lime areas, BrewLOGIC® technology calculates flow rate and adjusts brew time to maintain consistent pot levels
- Electronic diagnostics and built-in tank drain make service easier
- Ensure coffee quality with programming for brew level, cold brew lock- out and tank temperature, set easily from the front of the machine
- Coffee extraction controlled with programmable pre-infusion, pulse brew and digital temperature control
- Large 200oz. (5.9L) tank provides back-to-back brewing capacity
- Accepts thermal carafe up to 8.5" (21.6 cm) tall
- Energy-saver mode reduces tank temperature during idle periods
- Hot water faucet
- SplashGard® funnel deflects hot liquids away from the hand
- Dual voltage adaptable (Can operate at 120V/15 amp or 120/208-240V/20 amp)
- Use in quick turn environments where high quality coffee is continuously refreshed
- PROP 65 Warning Decal included in packaging with equipment
- Servers not included unless otherwise noted

#### Agency:





#### **Specifications**

Product #: 38700.0011 Faucet: Upper DB

Water Access: Plumbed

Finish: Stainless
Funnel: Black Plastic

# Electrical & Capacity

Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H <sup>2</sup> O Temp.	Phase	# Wires plus Ground	Hertz
120	12.5	1500	Yes	NEMA 5-15P	67	60°F (15.5°C)	1	2	60
120/208	13	2680	-	N/A	121	60°F (15.5°C)	1	3	60
120/240	15	3550	-	N/A	121	60°F (15.5°C)	1	3	60

\*When a BUNN is machine rated 120/208-240V, 120/208V or 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

#### Plumbing Requirements

	· · · · · · · · · · · · · · · · · · ·						
PSI		kPa	Fitting Supplied	Water Flow Required (GPM)			
	20-90	138-621	1/4" Male Flare Fitting	-			

## **CAD Drawings**

**Additional Features** 

2D	Revit	KLC
•		

**WARNING:** This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Unit				Shipping				
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	17.8 in.	9.0 in.	22.5 in.	24.8 in.	11.9 in.	25.9 in.	31.650 lbs	4.401 ft <sup>3</sup>
Metric	45.2 cm	22.9 cm	57.2 cm	62.9 cm	30.2 cm	65.7 cm	14.356 kgs	0.125 m³



## Related Products & Accessories: AXIOM®-DV-TC(38700.0011)



FUNNEL W/DECAL,PPK NAR BLK(SM)

Product #: 02774.0011



FUNNEL W/DECAL,PPK NAR BLK(LG)

Product #: 04274.0012



FILTERS,REGULAR1M 500/2 50/CL

Product #: 20115.0000



FUNNEL ASSY, SST-BLK HDL(7.12

Product #: 20216.0000



FUNNEL W/DECALS, BLACK PLASTIC

Product #: 20583.0003



FUNNEL ASSY, SST-PP BLK HNDL

Product #: 29151.0000



FUNNEL ASSY,SST-PP ORANGE HDL

Product #: 29151.0001



WATER FILTER SYSTEM,EQ-17-TL

Product #: 30200.1000



WATER FILTER,IN LINE ED-17-TL

Product #: 30201.1001



SYSTEM, WEQ-10(1.5)5L

Product #: 56000.0024



CARTRIDGE, WEQ-10 (1.5)5L

Product #: 56000.0121





## Serving & Holding Options: AXIOM®-DV-TC(38700.0011)



THERMAL CARAFE, BLK 1.9L 12PK

Product #:36029.0000



THERMAL CARAFE, BLK 1.83 L 1PK

Product #:36029.0001



THERMAL CARAFE,ORN 1.9L 12PK

Product #:36252.0000



THERMAL CARAFE,ORN 1.9L 1PK

Product #:36252.0001



CARAFE,SST 1.9L SHRT BLK 1

Product #:40163.0000